



LINUX MINT 22 · CINNAMON · APT · FLATPAK

Linux Mint Handbook

For advanced users

Run the system from the inside. APT and dpkg in depth, PPAs and Software Sources, upgrading to a new Mint release, systemd, AppArmor, ufw, Timeshift from the terminal, NVIDIA drivers and recovering a system that won't boot.

CONTENTS

1. APT in depth
2. dpkg queries
3. Software Sources, mirrors and PPAs
4. Upgrading to a new Mint release
5. Timeshift from the terminal
6. Firewall: ufw
7. AppArmor
8. systemd services
9. Logs: journalctl
10. Networking: nmcli, ip, ss
11. Users and permissions
12. SSH
13. Disks, swap and snapshots
14. Kernel, GRUB and booting
15. Drivers: NVIDIA and hardware acceleration
16. Podman, Docker, Distrobox
17. Text processing and pipelines
18. Archives, backups, syncing
19. Customizing the shell
20. Performance and power
21. Troubleshooting and recovery

Yellow italic text (like *<package>*) marks the parts you fill in. In the terminal, paste is Ctrl+Shift+V and copy is Ctrl+Shift+C. Commands that start with **sudo** change the system; read what they do before running them.



sudogrimoire.com/mint/

Free, searchable handbooks for Linux, Windows and macOS

APT in depth

APT settings live in `/etc/apt/apt.conf.d/`, repository definitions in `/etc/apt/sources.list.d/`, pinning rules in `/etc/apt/preferences.d/`.

```
$ apt policy <package>
```

Installed version, candidate version, which repository it comes from and priorities.

```
$ apt-cache madison <package>
```

All versions available in the repositories.

```
$ sudo apt install <package>=<version>
```

Installs a specific version (also used to downgrade).

```
$ sudo apt-mark hold <package>
```

Holds a package back from upgrades. `unhold` releases it, `showhold` lists holds.

```
$ apt-mark showmanual
```

Packages you installed yourself (not pulled in as dependencies).

```
$ apt-cache depends <package>
```

A package's dependencies. Reverse: `apt-cache rdepends --installed <package>`.

```
$ sudo apt install --no-install-recommends  
<package>
```

Installs without the extra Recommends packages.

```
$ sudo apt install apt-file && sudo apt-file  
update
```

Lets you search the files of packages that aren't installed.

```
$ apt-file search <file-name>
```

Finds which package provides a file or command.

```
$ less /var/log/apt/history.log
```

APT history: what was installed or removed, and when. Older entries: `zless history.log.1.gz`.

```
$ sudo apt clean
```

Empties the downloaded package cache (`/var/cache/apt/archives`). `autoclean` removes only obsolete ones.

```
$ sudo dpkg-reconfigure <package>
```

Asks a package's setup questions again.
Examples: `tzdata`, `locales`, `keyboard-configuration`.

```
$ sudo apt install needrestart
```

Tells you which services need restarting after updates.

```
$ sudo apt install unattended-upgrades && sudo  
dpkg-reconfigure -plow unattended-upgrades
```

Installs security updates automatically. Logs are under `/var/log/unattended-upgrades/`.

```
$ apt modernize-sources
```

Converts old one-line `sources.list` files to the new deb822 (`.sources`) format (APT 3.0 and later; run with `sudo`).

dpkg queries

`dpkg` is the low-level package tool underneath APT. Install with APT; `dpkg` is ideal for queries and repairs.

```
$ dpkg -l | grep <word>
```

Lists installed packages with their state (ii = installed, rc = removed but config remains).

```
$ dpkg -L <package>
```

Files of an installed package.

```
$ dpkg -S <file-path>
```

Tells you which package a file belongs to.
Example: `dpkg -S /usr/bin/ls`.

```
$ dpkg -s <package>
```

A package's status, version and dependencies.

```
$ sudo dpkg --configure -a
```

Finishes interrupted installations (the "dpkg was interrupted" error).

```
$ sudo apt --fix-broken install
```

Fixes a broken state by installing missing dependencies.

```
$ dpkg -l | awk '/^rc/{print $2}' | xargs -r  
sudo apt purge -y
```

Cleans up config files left over from removed packages.

```
$ dpkg-query -W -f='${Installed-  
Size}\t${Package}\n' | sort -n | tail -20
```

The 20 largest packages (KB).

```
$ sudo dpkg --add-architecture i386 && sudo apt  
update
```

Enables 32-bit packages (for Steam, Wine).

```
$ sudo apt install debsums && sudo debsums -s
```

Checks package files for corruption; prints only problems.

Software Sources, mirrors and PPAs

Mint keeps its own repositories and Ubuntu's base repositories in `/etc/apt/sources.list.d/official-package-repositories.list`. Software Sources changes them with the mouse.

Menu > Software Sources

Choose a fast mirror for Mint and for the base, add PPAs, enable source code and backports.

Software Sources > Maintenance

Fix MergeList problems, add missing keys, remove duplicate sources, downgrade foreign packages.

```
$ sudo add-apt-repository ppa:<user>/<ppa>
```

Adds a PPA from the terminal, installs its key and refreshes the package list.

```
$ sudo add-apt-repository --remove ppa:
<user>/<ppa>
```

Removes a PPA; installed packages stay as they are.

```
$ ls /etc/apt/sources.list.d/
```

Repository files.

```
$ curl -fsSL <key-URL> | sudo gpg --dearmor -o
/etc/apt/keyrings/<name>.gpg
```

Adds a third-party repository's signing key.

WARNING PPAs aren't reviewed by Mint or Canonical; add only PPAs you trust. Use PPAs built for Ubuntu 24.04 ("noble").

Upgrading to a new Mint release

Point releases (22.1, 22.2, 22.3) arrive as an Update Manager menu item. A new major version (for example 21 to 22) uses the mintupgrade tool.

Update Manager > Edit >

Upgrade to Linux Mint 22.x

Appears when a new point release is out. Take a Timeshift snapshot first.

```
$ sudo apt install mintupgrade
```

Installs the major upgrade tool.

```
$ sudo mintupgrade
```

Checks the system, takes a snapshot and upgrades to the next major version step by step.

```
$ cat /etc/linuxmint/info
```

The installed Mint release and edition.

TIP Read the release notes on linuxmint.com before a major upgrade; a fresh install is often just as quick.

Timeshift from the terminal

Timeshift works from the terminal too, which helps when the desktop no longer starts.

```
$ sudo timeshift --list
```

Lists snapshots.

```
$ sudo timeshift --create --comments "<note>"
```

Takes a snapshot now.

```
$ sudo timeshift --restore
```

Restores a snapshot; it asks which one and where.

```
$ sudo timeshift --delete --snapshot '<name>'
```

Deletes one snapshot.

TIP Timeshift doesn't back up your personal files by default. Use Backup Tool (mintbackup) or another backup for your home folder.

Firewall: ufw

Linux Mint ships with ufw and its graphical front end (Firewall Configuration) installed but disabled. ufw (Uncomplicated Firewall) is a simple front end to nftables.

```
$ sudo ufw status verbose
```

Status and rules.

```
$ sudo ufw default deny incoming && sudo ufw  
default allow outgoing
```

Block incoming, allow outgoing (a sensible desktop default).

```
$ sudo ufw enable
```

Turns the firewall on and keeps it on at boot.

```
$ sudo ufw allow ssh
```

Allows SSH (22). `sudo ufw limit ssh` slows down brute-force attempts.

```
$ sudo ufw allow 8080/tcp
```

Opens a port.

```
$ sudo ufw allow from 192.168.1.0/24 to any port  
445
```

Allows a port only from the local network.

```
$ sudo ufw status numbered
```

Lists rules with numbers.

```
$ sudo ufw delete <number>
```

Deletes a rule by number.

```
$ sudo ufw app list
```

Ready-made app profiles defined by packages.

```
$ sudo apt install gufw
```

Graphical interface.

WARNING Docker writes its own iptables/nftables rules, so ports it publishes bypass ufw. If you use Docker, bind ports to localhost like `127.0.0.1:8080:80`.

AppArmor

Linux Mint limits what programs can access with AppArmor profiles. If a program says “Permission denied” while file permissions look right, AppArmor may be the cause.

```
$ sudo aa-status
```

Loaded profiles and their mode (enforce / complain).

```
$ sudo journalctl -k --grep=apparmor
```

Operations AppArmor blocked (“DENIED” lines).

```
$ sudo apt install apparmor-utils
```

Installs aa-complain, aa-enforce, aa-logprof and friends.

```
$ sudo aa-complain /etc/apparmor.d/<profile>
```

Puts a profile in log-only mode (for diagnosis).

```
$ sudo aa-enforce /etc/apparmor.d/<profile>
```

Puts a profile back into enforcing mode.

```
$ sudo aa-logprof
```

Looks at the logged denials and interactively suggests rules to add.

```
$ sudo apparmor_parser -r  
/etc/apparmor.d/<profile>
```

Reloads an edited profile. Local additions go under `/etc/apparmor.d/local/`.

systemd services

systemd manages services (background daemons), timers and the boot process.

```
$ systemctl status <service>
```

Shows status, the latest log lines and the PID.

```
$ sudo systemctl start|stop|restart <service>
```

Starts / stops / restarts a service.

```
$ sudo systemctl enable --now <service>
```

Starts it at boot and starts it now.

```
$ sudo systemctl disable --now <service>
```

Stops it from starting at boot and stops it now.

```
$ sudo systemctl mask <service>
```

Prevents the service from being started at all.
`unmask` undoes it.

```
$ systemctl --failed
```

Lists failed units.

```
$ systemctl list-units --type=service --  
state=running
```

Running services.

```
$ systemctl list-unit-files --state=enabled
```

Units that start at boot.

```
$ systemctl list-timers
```

Scheduled jobs (systemd's answer to cron).

```
$ systemctl cat <service>
```

Shows the unit file and any drop-ins.

```
$ sudo systemctl edit <service>
```

Creates an override (drop-in) without touching the packaged file.

```
$ sudo systemctl daemon-reload
```

Makes systemd reread unit files after you change them.

```
$ systemctl --user enable --now <service>
```

User services; definitions live under
`~/.config/systemd/user/`.

```
$ loginctl enable-linger $USER
```

Lets user services run even when you are not logged in.

```
$ systemd-analyze blame
```

Lists how long each service took at boot.

```
$ systemd-analyze critical-chain
```

Shows the critical path of the boot.

Logs: journalctl

System logs are kept in the systemd journal. Linux Mint also has rsyslog installed; the same messages are written to `/var/log/syslog`.

```
$ journalctl -b
```

Everything since this boot.

```
$ journalctl -b -1 -p err
```

Errors from the previous boot. The first place to look after a crash.

```
$ journalctl -u <service> -f
```

Follows a service's log live.

```
$ journalctl -p warning --since "1 hour ago"
```

Warnings and worse from the last hour.

```
$ journalctl --since today --grep "<word>"
```

Searches today's log for text.

```
$ journalctl -k
```

Kernel messages only (like dmesg).

```
$ journalctl --list-boots
```

Lists recorded boots.

```
$ journalctl --disk-usage
```

Space used by the logs.

```
$ sudo journalctl --vacuum-time=2weeks
```

Deletes logs older than two weeks. `--vacuum-size=500M` also works.

```
$ coredumpctl list
```

Records of crashed programs (if systemd-coredump is installed). `coredumpctl info <PID>` gives details.

```
$ sudo dmesg -w
```

Follows the kernel ring buffer live (to see what happens when you plug in USB).

Networking: nmcli, ip, ss

On desktop installs NetworkManager runs the network; its command-line tool is `nmcli` and its text UI is `nmtui`.

```
$ nmcli device status
```

Network devices and their state.

```
$ nmcli device wifi list
```

Visible Wi-Fi networks with signal strength.

```
$ nmcli device wifi connect "<SSID>" password "<password>"
```

Connects to a Wi-Fi network.

```
$ nmcli connection show
```

Saved connections.

```
$ nmcli connection up|down "<name>"
```

Brings a connection up / down.

```
$ sudo nmcli connection modify "<name>"  
ip4.method manual ip4.addresses  
192.168.1.50/24 ip4.gateway 192.168.1.1  
ip4.dns "1.1.1.1 9.9.9.9"
```

Sets a static IP. Then `nmcli connection up "<name>"`.

```
$ nmtui
```

Menu-driven text UI; useful without a graphical desktop.

```
$ sudo hostnamectl set-hostname <new-name>
```

Changes the computer's name.

```
$ ip -br a
```

Interfaces and IP addresses, briefly.

```
$ ip route
```

Routing table and default gateway.

```
$ resolvectl status
```

DNS servers (when systemd-resolved is used). Otherwise `cat /etc/resolv.conf`.

```
$ ss -tulpn
```

Listening TCP/UDP ports and which program owns them (sudo to see the program).

```
$ ping -c 4 <address>
```

Reachability test.

```
$ tracepath <address>
```

The route packets take.

```
$ curl -I https://<site>
```

Fetches a site's HTTP headers.

```
$ dig <domain>
```

DNS lookup (bind9-dnsutils package).

Users and permissions

On this system sudo rights come from membership in the `sudo` group.

```
$ id
```

Your user ID and groups.

```
$ sudo useradd -m -G sudo -s /bin/bash <user>
```

New user with a home folder and sudo rights.
Then `sudo passwd <user>`.

```
$ sudo usermod -aG <group> <user>
```

Adds a user to a group (without `-a` it removes them from other groups). Takes effect after logging in again.

```
$ sudo userdel -r <user>
```

Deletes a user along with their home folder.

```
$ passwd
```

Changes your own password.

```
$ chmod +x <file>
```

Makes a file executable.

```
$ chmod 644 <file>
```

Owner reads/writes, others read. 755 is typical for folders and scripts.

```
$ chmod -R u+rwX,go-rwx <folder>
```

Makes a folder accessible only to its owner.

```
$ sudo chown -R <user>:<group> <path>
```

Changes the owner.

```
$ setfacl -m u:<user>:rw <file>
```

Gives a specific user extra permissions (ACL).
`getfacl` shows them.

```
$ sudo -i
```

Opens a root shell. Type exit when done.

```
$ sudo visudo -f /etc/sudoers.d/<name>
```

Edits sudo rules with syntax checking.

TIP On Mint the root account has no password (it is locked); use `sudo -i` for a root shell.

SSH

```
$ sudo apt install openssh-server
```

Installs the SSH server; the service (ssh) starts automatically. Status: `systemctl status ssh`.

```
$ ssh-keygen -t ed25519 -C "<Label>"
```

Creates a key pair (`~/.ssh/id_ed25519`).

```
$ ssh-copy-id <user>@<server>
```

Uploads your public key to the server; after that you log in without a password.

```
$ ssh <user>@<server> -p <port>
```

Connects.

```
$ ssh -L 8080:localhost:80 <user>@<server>
```

Tunnels local port 8080 to port 80 on the server.

```
$ scp <file> <user>@<server>:~/
```

Copies a file to the server. `-r` for folders.

TIP Define short names in `~/.ssh/config` :

```
Host myserver · HostName 192.168.1.10 · User user · IdentityFile ~/.ssh/id_ed25519
```

Then just `ssh myserver`.

TIP To turn off password logins, write `PasswordAuthentication no` into `/etc/ssh/sshd_config.d/10-local.conf` and restart the SSH service.

Disks, swap and snapshots

Linux Mint uses ext4 by default. Timeshift is the most common tool for system snapshots: it works in rsync mode on ext4, and in btrfs mode on Btrfs with Ubuntu-style `@ / @home` subvolumes.

```
$ sudo apt install timeshift
```

Installs Timeshift; on first launch a wizard asks for the target disk and schedule.

```
$ sudo timeshift --create --comments "  
<description>"
```

Takes a snapshot manually. A good habit before a big update.

```
$ sudo timeshift --list
```

Lists snapshots.

```
$ sudo timeshift --restore
```

Interactive restore. It can also run from a live USB if the system won't boot.

```
$ lsblk -f && findmnt /
```

Disks, file systems and where root is mounted.

```
$ sudoedit /etc/fstab
```

Disks mounted at boot. `sudo blkid` gives the UUIDs. A mistake breaks booting; test with `sudo mount -a` afterwards.

```
$ swapon --show
```

Active swap areas.

```
$ sudo fallocate -l 4G /swapfile && sudo chmod  
600 /swapfile && sudo mkswap /swapfile && sudo  
swapon /swapfile
```

Creates a 4 GB swap file. To make it permanent, add `/swapfile none swap sw 0 0` to fstab.

```
$ sudo apt install systemd-zram-generator
```

Compressed swap in RAM (zram); configure it in `/etc/systemd/zram-generator.conf`.

```
$ sudo apt install smartmontools && sudo  
smartctl -a /dev/<sda>
```

Disk health report (SMART). For NVMe use `/dev/nvme0`.

```
$ sudo tune2fs -l /dev/<sda2> | grep -i -E  
'state|mount count'
```

State of an ext4 partition.

WARNING Don't run `fsck` on a mounted partition. To check the root partition, boot from a live USB, or add `fsck.mode=force` to the kernel line in GRUB for one boot.

Kernel, GRUB and booting

GRUB settings are in `/etc/default/grub` ; run `update-grub` after changing them. The kernel metapackage is `linux-generic` , the headers are `linux-headers-generic` .

```
$ dpkg --get-selections 'linux-image*' | grep ^ii
```

Installed kernels.

```
$ uname -r
```

Running kernel.

```
$ sudoedit /etc/default/grub
```

GRUB settings. To always show the menu:

`GRUB_TIMEOUT_STYLE=menu` and

`GRUB_TIMEOUT=5` .

```
$ sudo update-grub
```

Regenerates the GRUB configuration.

TIP To add a kernel parameter, append it to the `GRUB_CMDLINE_LINUX_DEFAULT="quiet splash"` line in `/etc/default/grub` , then run `sudo update-grub` .

```
$ cat /proc/cmdline
```

Parameters of the running kernel.

```
$ sudo update-initramfs -u
```

Rebuilds the initramfs for the running kernel. For all kernels: `-u -k all` .

```
$ sudo apt install linux-headers-generic
```

Kernel headers for building drivers (DKMS).

```
$ dkms status
```

Modules built with DKMS (NVIDIA, VirtualBox, Wi-Fi) and which kernels they were built for.

```
$ mokutil --sb-state
```

Whether Secure Boot is on.

```
$ sudo mokutil --import /var/lib/dkms/mok.pub
```

Enrolls the DKMS signing key in MOK. Set a password; after rebooting choose "Enroll MOK" on the blue screen.

```
$ lsmod | grep <module>
```

Loaded kernel modules. `modinfo` for details, `sudo modprobe` to load.

Install or remove kernel versions with the mouse;
newer HWE kernels are listed here too.

Drivers: NVIDIA and hardware acceleration

Mint's Driver Manager is the easy way; under the hood it uses Ubuntu's `ubuntu-drivers` tool.

Menu > Driver Manager

Shows the drivers for your hardware and marks the recommended one.

```
$ ubuntu-drivers list
```

Drivers available for your hardware.

```
$ sudo ubuntu-drivers install
```

Installs the recommended driver.

```
$ nvidia-smi
```

GPU status and usage.

```
$ sudo apt install vainfo && vainfo
```

Verifies VA-API hardware video acceleration.

```
$ lspci -k | grep -A 3 -E "VGA|3D"
```

The graphics card and the kernel driver in use.

```
$ sudo apt install steam-installer
```

Steam (it adds the 32-bit architecture itself).

WARNING Don't install the NVIDIA driver from the `.run` file on [nvidia.com](https://www.nvidia.com); it breaks on kernel updates and conflicts with the package manager.

Podman, Docker, Distrobox

Distrobox lets you use other distributions' tools without cluttering the host; Podman or Docker run services. Podman is largely compatible with Docker commands and doesn't need root.

```
$ sudo apt install podman distrobox
```

Installs Podman and Distrobox.

```
$ distrobox create -i  
registry.fedoraproject.org/fedora:latest -n  
<name>
```

Creates a container of another distribution (e.g. `-i archlinux`, `-i ubuntu:24.04`).

```
$ distrobox enter <name>
```

Enters it; your home folder is shared. Inside, `distrobox-export --app <app>` adds the app to the host menu.

```
$ podman run -it --rm debian bash
```

Starts a throwaway container.

```
$ podman ps -a
```

All containers.

```
$ podman images
```

Local images. `podman system prune -a` removes unused ones.

```
$ podman run -d -p 8080:80 -v  
~/site:/usr/share/nginx/html  
docker.io/library/nginx
```

Runs a service with a mounted folder.

```
$ sudo apt install docker.io docker-compose-v2
```

Installs Docker from the Ubuntu repositories Mint uses. For Docker's own repository, follow its Ubuntu "noble" instructions.

```
$ sudo usermod -aG docker $USER
```

Use Docker without sudo (log in again). This group is equivalent to root access.

TIP To run a Podman container as a systemd service, use Quadlet: write a `.container` file under `~/.config/containers/systemd/`, run `systemctl --user daemon-reload` and start it.

Text processing and pipelines

| passes one command's output to the next. > writes to a file (overwriting), >> appends, 2>&1 sends errors to the same place. && runs if the previous command succeeded, || if it failed.

```
$ grep -rni "<text>" <folder>
```

Recursive, case-insensitive search with line numbers.

```
$ grep -v "^#" <file> | grep -v "^$"
```

Drops comments and blank lines; handy for reading config files.

```
$ sed -i 's/<old>/<new>/g' <file>
```

Find and replace in a file. Try without -i first and check the output.

```
$ awk '{print $1, $3}' <file>
```

Prints the 1st and 3rd column of each line.

```
$ sort <file> | uniq -c | sort -rn | head
```

Most frequently repeated lines.

```
$ wc -l <file>
```

Line count.

```
$ cut -d: -f1 /etc/passwd
```

First colon-separated field (user names).

```
$ find . -name "*.log" -mtime +7 -delete
```

Deletes .log files older than 7 days.

```
$ find . -type f -name "*.jpg" -print0 | xargs  
-0 -I{} cp {} ~/Pictures/
```

Copies found files one by one (safe with spaces in names).

```
$ <command> | tee <file>
```

Writes output to both the screen and a file.

```
$ echo "<line>" | sudo tee -a /etc/<file>
```

Appends to a root-owned file (sudo echo >> doesn't work).

```
$ diff -u <old> <new>
```

Differences between two files.

```
$ watch -n 2 <command>
```

Reruns a command every 2 seconds.

```
$ curl -s <URL> | jq '.'
```

Pretty-prints JSON (jq package).

Archives, backups, syncing

```
$ tar -czvf <archive>.tar.gz <folder>
```

Archives a folder with gzip.

```
$ tar --zstd -cvf <archive>.tar.zst <folder>
```

Archives with zstd; faster than gzip and compresses better.

```
$ tar -xvf <archive>
```

Extracts any tar archive. Use `-C <folder>` for a target folder.

```
$ tar -tvf <archive>
```

Lists the contents without extracting.

```
$ zip -r <archive>.zip <folder>
```

Creates a zip. Extract with `unzip <archive>.zip`.

```
$ 7z x <archive>.7z
```

Extracts 7z / rar and similar formats (7zip package).

```
$ rsync -avh --progress <source>/ <target>/
```

Syncs a folder; copies only what changed. The trailing / means "the contents".

```
$ rsync -avh --delete --dry-run <source>/  
<target>/
```

Mirror, deleting from the target what's not in the source; see what would happen first with `--dry-run`.

```
$ rsync -avz -e ssh <source>/ <user>@<server>:  
<path>/
```

Remote backup over SSH.

```
$ rclone config
```

Sets up cloud targets such as Google Drive, OneDrive and S3; sync with `rclone sync`.

Customizing the shell

Bash settings live in `~/.bashrc` in your home folder. Add aliases and variables at the end of the file.

```
$ nano ~/.bashrc
```

Opens the shell configuration file.

```
alias update='sudo apt update && sudo apt  
upgrade && flatpak update'
```

System update in one word. Write it into the file and save.

```
alias ll='ls -lah --group-directories-first'
```

A handy detailed listing.

```
$ source ~/.bashrc
```

Loads the changes without opening a new terminal.

```
export PATH="$HOME/.local/bin:$PATH"
```

Adds your own scripts folder to PATH.

```
$ echo $SHELL
```

The shell you are using.

```
$ sudo apt install zsh && chsh -s /usr/bin/zsh
```

Installs Zsh and makes it the default (log in again). Same method for Fish.

```
$ type <command>
```

Shows whether a name is an alias, a function or a file.

TIP When writing a script, put `#!/usr/bin/env bash` on the first line and `set -euo pipefail` on the second; it stops on errors and catches undefined variables. Then `chmod +x script.sh`.

Performance and power

Cinnamon shows power profiles in the power applet when power-profiles-daemon is installed.

```
$ powerprofilesctl list
```

Power profiles and which one is active (power-profiles-daemon).

```
$ powerprofilesctl set performance
```

Switches profile: power-saver / balanced / performance.

```
$ sudo apt install lm-sensors
```

CPU and disk temperatures; run `sensors` after installing.

```
$ sudo apt install btop nvidia-smi
```

Advanced system and GPU monitors.

```
$ sudo iotop -o
```

Processes writing the most to disk (iotop package).

```
$ systemd-analyze
```

Total boot time (firmware, loader, kernel, userspace).

```
$ sudo fstrim -av
```

Runs TRIM on SSDs. To do it weekly: `sudo systemctl enable --now fstrim.timer`.

```
$ upower -i $(upower -e | grep BAT)
```

Battery health, capacity and charge information.

```
$ free -h && swapon --show
```

RAM and swap areas.

Troubleshooting and recovery

What to try, in order, when the system won't boot or an update broke something.

TIP 1. Boot an older kernel. In GRUB, pick the previous kernel under “Advanced options for Linux Mint”. If the menu doesn't appear, press Esc (UEFI) or Shift (BIOS) while booting.

TIP 2. Switch to a text console. Ctrl+Alt+F3 (F2–F6). Log in and check errors with `journalctl -b -p err`.

```
$ sudo systemctl restart display-manager
```

Restarts the graphical login manager (GDM, SDDM, LightDM); the open session closes.

```
$ sudo dpkg --configure -a && sudo apt --fix-broken install
```

Finishes interrupted updates.

TIP 3. Recovery mode. GRUB > Advanced options > the “(recovery mode)” entry. Choose “root” from the menu to get a shell; if root is mounted read-only, run `mount -o remount,rw /`.

TIP 4. chroot from a live USB. Boot a live USB and run the following in a terminal, in order. Adjust disk names to your system using `lsblk`.

```
$ sudo mount /dev/<sda2> /mnt && sudo mount /dev/<sda1> /mnt/boot/efi
```

Mounts the root and EFI partitions (add `-o subvol=@` for Btrfs).

```
$ for d in dev proc sys run; do sudo mount --rbind /$d /mnt/$d; done && sudo chroot /mnt
```

Switches into the installed system; apt, update-grub and update-initramfs work inside.

```
$ grub-install && update-grub
```

Reinstalls the boot loader inside the chroot (on UEFI systems).

```
$ sudo timeshift --restore
```

If Timeshift is installed, you can return to the last good snapshot from a live USB.

Commands are written for Linux Mint 22 Cinnamon (based on Ubuntu 24.04 LTS; APT, Flatpak). Most of them also work on the Xfce and MATE editions. Menu names follow the English interface. Commands that start with `sudo` change the system; read what they do before running them.